



12.5MM PLASTERBOARD, SCREWED TO FURRING STRIPS WITHIN EPS, OR ALTERNATIVELY SPOT & DAB WITH PROPRIETARY ADHESIVE & SCREW FIX THE HEAD OF THE PLASTERBOARD SHEET AT 600MM MIN. CTRS (MIN. TWO FIXINGS) BACK TO FURRING STRIPS.

IN THE UK, SOME AREAS ARE DESIGNATED AS 'VERY SEVERE WEATHER LOCATIONS' ALL AS NOTED IN THE APPROVED DOCUMENTS. IN THIS INSTANCE THERE NEEDS TO BE A 25MM OVERLAP IN THE CONSTRUCTION TO MASK THE JOINT BETWEEN THE WINDOW FRAME AND THE WALL CONSTRUCTION, AS INDICATED IN THE DETAILS ABOVE & BELOW.

NOTE: ALTHOUGH IT MAY NOT BE NECESSARY FOR REINFORCEMENT TO BE INCORPORATED FOR STRUCTURES UP TO THREE STOREYS IN HEIGHT, STRUCTURES UP TO FOUR STOREYS AND INDIVIDUAL SITE CONDITIONS MAY DICTATE OTHERWISE & THEREFORE AN ENGINEER / ARCHITECT SHOULD BE CONSULTED IN THESE CIRCUMSTANCES. ALL DETAILS ARE TO CONSTRUCTED IN ACCORDANCE WITH CURRENT BUILDING CODES AND REGULATIONS. POLYSTEEL UK RESERVES THE RIGHT TO CHANGE INFORMATION SHOWN WITHOUT NOTICE

POLYSTEEL



POLYSTEEL **Reveal Detail for:**
Severe weather conditions using treated timber

SCALE: 1:5

APPROVED BY:

DRAWN BY: CSW

DATE: MAY 2005

REVISED: 08/03/19

Copyright 2005

DRWG. No.

POLYSTEEL UK Ltd

07/DET01

Tel: 01722 446 594

www.polysteel.co.uk