



12.5MM PLASTERBOARD, SCREWED TO FURRING STRIPS WITHIN EPS, OR ALTERNATIVELY SPOT & DAB WITH PROPRIETARY ADHESIVE & SCREW FIX THE HEAD OF THE PLASTERBOARD SHEET AT 600MM MIN. CTRS (MIN. TWO FIXINGS) BACK TO FURRING STRIPS.

NOTE: ALTHOUGH IT MAY NOT BE NECESSARY FOR REINFORCEMENT TO BE INCORPORATED FOR STRUCTURES UP TO THREE STOREYS IN HEIGHT, STRUCTURES UP TO FOUR STOREYS AND INDIVIDUAL SITE CONDITIONS MAY DICTATE OTHERWISE & THEREFORE AN ENGINEER / ARCHITECT SHOULD BE CONSULTED IN THESE CIRCUMSTANCES. ALL DETAILS ARE TO CONSTRUCTED IN ACCORDANCE WITH CURRENT BUILDING CODES AND REGULATIONS. POLYSTEEL UK RESERVES THE RIGHT TO CHANGE INFORMATION SHOWN WITHOUT NOTICE

**POLYSTEEL**



**POLYSTEEL**

**Typical Reveal Detail using treated timber buck**

SCALE: 1:5

APPROVED BY:

DRAWN BY: CSW

DATE: MAY 2005

REVISED: 08/03/19

Copyright 2005

**POLYSTEEL UK Ltd**

DRWG. No.

**07/DET02**

Tel: 01722 446 594

www.polysteel.co.uk