

POLYSTEEL LINTEL
AS REQUIRED, FOR
REQUIREMENT REFER TO
LINTEL TECHNICAL SHEET

50MM PRESSURE
TREATED
TIMBER WINDOW BLOCK
OUT

METAL LINTEL TO SUPPORT
BRICKWORK OVER APERTURES.
SIZE AS RECOMMENDED BY
ENGINEER OR MANUFACTURER

WINDOW JAMB FINISHED
WITH 12.5MM PLASTERBOARD

SLOTS LEFT OUT IN SILL TIMBER
TO ALLOW CONCRETE TO BE
COMPLETELY PLACED

50MM PRESSURE TREATED
TIMBER WINDOW BLOCK OUT

CILL BOARD

EXTERIOR FINISH
INDICATING
BRICKWORK.

12.5MM PLASTERBOARD

150 TO 200MM

NOTE: ALTHOUGH IT MAY NOT BE NECESSARY FOR REINFORCEMENT TO BE INCORPORATED FOR STRUCTURES UP TO THREE STOREYS IN HEIGHT, STRUCTURES UP TO FOUR STOREYS AND INDIVIDUAL SITE CONDITIONS MAY DICTATE OTHERWISE & THEREFORE AN ENGINEER / ARCHITECT SHOULD BE CONSULTED IN THESE CIRCUMSTANCES. ALL DETAILS ARE TO CONSTRUCTED IN ACCORDANCE WITH CURRENT BUILDING CODES AND REGULATIONS. POLYSTEEL UK RESERVES THE RIGHT TO CHANGE INFORMATION SHOWN WITHOUT NOTICE

POLYSTEEL



Tel: 01722 446 594

www.polysteel.co.uk

**POLYSTEEL Window head and cill
with Pressure treated timber Block out**

SCALE: 1:10

APPROVED BY:

DRAWN BY: CSW

DATE: MAY 2005

REVISED: 08/03/19

Copyright 2005

POLYSTEEL UK Ltd

DRWG. No.

07/DET06